



Airflow monitoring system for Tantec PlasmaTEC-X extraction system

Monitoring and detection of extraction performance

Are you concerned about whether your extraction solution will continue to work optimally after setup?

The airflow monitoring system for the FlensTech extraction system was developed to make your processes controllable. With a good extraction solution, a high level of process and work safety can be achieved. In most cases there is no monitoring of the extraction power. Pressure fluctuations in the piping system can reduce the effectiveness of the extraction.

A pressure sensor connected to the control box continuously measures the line pressure. At an adjustable limit value, a contact is switched over, which can be used for signalling or control.

The monitoring is prepared for the PlasmaTEC-X generators from Tantec A/S in combination with the FlensTech extraction system. In this way, the generators provide the power supply for the connected devices.

In addition, the control box has a pre-

assembled lead for the I/O input of the generator, which allows it to be switched off automatically if the limit value is undercut.

Since the I/O input is occupied by the airflow monitoring system, all signals for PLC operation are provided in the control box. This also allows for easy retrofitting of the monitoring system in existing systems.

The system can be expanded with a light tower. With this, the system status can be recognised quickly, visually and at a great distance in a production facility.

At a glance:

- Monitoring the extraction volume
- Efficient protection for people, products and machines
- Increase in process reliability
- Cost-efficient no waste of room air
- Plug & Play for Tantec
 PlasmaTEC-X applications
- Easy integration into existing systems
- Individual adaptions on request

Tantec A/S Industrivej 6

DK-6640 Lunderskov

Contact

sales@tantec.com (+45) 7558 5822

Online

www.tantec.com



Technical data



Plasma & Corona

Control ports

Plug & Play und PLC interface

Pressure monitoring

Pressure display on LCD display and measured value output

Light tower

Quick identification of the system status



Attachments

Connecting the sensor to the FlensTech suction hood

Supply and control

Pre-assembled connections for Tantec PlasmaTEC-X

Scope of delivery

F830415

Airflow monitoring system incl. control lines for PlasmaTEC-X

Incl. pressure sensor and connection accessories

Optionally available: signal light and further pressure sensors

www.tantec.com